



→ Product Website

→ Experience in AR

27" Office Monitor

With an impressive 27-inch diagonal and a resolution of 2560 x 1440 pixels, the EV2760 offers all the space that's needed for efficient use in the office. No matter if it's text, graphics or videos, users enjoy crystal clear, incredibly detailed image reproduction on its large screen. Anti-reflection coating, flicker-free brightness control and a flexible stand facilitate ergonomic work. Its smart, three-sided, virtually frameless design means that you focus on what's most important while maintaining a clear overview of your work. Thanks to its EcoView functions, it boasts a low power consumption if, for example, you need a lower brightness level and a glare-free view. The EV2760 offers a wide range of connection possibilities with Display Port, HDMI and DVI-D signal inputs – not to mention four USB downstream ports.

- 27-inch IPS LCD monitor with a resolution of 2560 x
 1440 pixels for excellent image quality
- Bezel only 1 mm for a compact and ultra-elegant design
- Flicker-free image reproduction thanks to hybrid brightness control
- Auto EcoView and EcoView Optimizer for maximum energy-efficiency and superb ergonomics
- Optimised anti-reflection properties and flexible positioning
- USB 3.1 hub with one upstream and four downstream ports
- 2 x DisplayPort, HDMI, DVI-D and D-Sub signal inputs
- Proven to be environmentally friendly and produced in a socially responsible way
- 5-year warranty for highest investment security





Technical Data

2760-BK 2760-WT ck ite itee xScan ge and medium-sized companies, Private user 8 all business, CAD, Finance, Control rooms ne, compatible with most computers and operating stems including macOS and Windows 25047055396 25047055402
ite ice xScan ge and medium-sized companies, Private user 8 all business, CAD, Finance, Control rooms ne, compatible with most computers and operating terms including macOS and Windows
xScan ge and medium-sized companies, Private user 8 all business, CAD, Finance, Control rooms ne, compatible with most computers and operating stems including macOS and Windows
ge and medium-sized companies, Private user 8 all business, CAD, Finance, Control rooms ne, compatible with most computers and operating stems including macOS and Windows
all business, CAD, Finance, Control rooms ne, compatible with most computers and operating stems including macOS and Windows
stems including macOS and Windows
5
)
7 x 336
60 x 1440
33 x 0,233
50 x 1440, 1920 x 1200, 1920 x 1080 (Full HD), 1680 x 50, 1600 x 1200, 1280 x 1024, 1024 x 768, 800 x 600, 0 x 400, 640 x 480
7 million colors (DVI, 8 Bit), 16.7 million colors (Dis- yPort, 8 Bit), 16.7 million colors (HDMI, 8 Bit)
re than 1.06 billion color tones /14-bit
GB
)
00:1
10:1

CONNECTIONS	
Signal inputs	2x DisplayPort (HDCP 1.3), HDMI (HDCP 1.4), DVI-D (HDCP 1.4)
USB specification	USB 5Gbps (USB 3)
USB upstream ports	1 x type B
USB downstream ports	4x type A
Graphic signal	DisplayPort, HDMI (RGB, YUV), DVI Dual Link (TMDS)
Sync formats	Separate
Audio input	3.5 mm stereo jack, DisplayPort, HDMI
Audio / headphone output	3.5 mm stereo jack

FEATURES & OPERATION

Preset color/greyscale modes	2x manual memory locations, sRGB, Paper, Movie, DICOM
DICOM tone curve	✓
Auto EcoView	✓
EcoView Index	✓
EcoView Optimizer	✓
Overdrive	✓
No flickering	✓
HDCP Decoder	✓
Automatic signal input recognition	✓
Imagen por imagen	✓
Built-in speakers	✓
On-screen menu languages	de, en, fr, es, it, se
Adjustment options	Color Mode, Brightness, Contrast, Color temperature /White point, Gamma, Overdrive, Colour tone, Color saturation, Resolution, Scaling, OSD language, Signal input, All EcoView functions, Volume
Button Guide	✓
Integrated power unit	✓

ELECTRICAL DATA

Frequency	DisplayPort: 31-89 kHz / 59-61Hz (69-71Hz); HDMI:31-89 kHz / 59-61Hz (29-31Hz, 49-51Hz, 69-71Hz); DVI-D: 31-89 kHz / 59-61Hz (29-31Hz, 69-71Hz)
Power consumption (typical) [in watts]	16
Maximum Power Consumption [in watts]	67 (at maximum brightness with all signal inputs and USB ports in use)
Max. Power consumption in stand-by mode [in watts]	0.5
Power consumption with power switch off [in watts]	0
Energy efficiency class	E
Energy consumption/1000h [in kWh]	18
Power supply	AC 100-240V, 50/60Hz
Power management	✓





DIMENSIONS & WEIGHT

Dimensions (incl. stand) (width x height x depth) [in mm]	611,7 x 376,3-545,3 x 230
Weight (incl. stand) [in kg]	8.5
Dimensions (without stand) (width x height x depth) [in mm]	611,7 x 364,4 x 53,7
Weight (without stand) [in kg]	5.7
Dimension drawing (PDF)	Dimension drawing (PDF)
Rotatability of the stand [in °]	344
Tiltability forwards/backwards [in °]	5 / 35
Pivot between portrait / landscape	clockwise and anti-clockwise
Height adjustment range [in mm]	169
Hole spacing	100 x 100

CERTIFICATION & STANDARDS

Certification	CE, UKCA, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified Generation 9, EPEAT
	2018 (US), TÜV/Low Blue Light Content, TÜV/Flicker
	Free, RCM, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S,
	PSE, VCCI-B, EPA ENERGY STAR, RoHS, WEEE, China
	RoHS, CCC, BIS, BSMI

SOFTWARE & ACCESSORIES

Accompanying software and other accessories are available for download	Screen InStyle
Other box contents	USB cable (Type A - Type B), Signal cable DisplayPort - DisplayPort, Manual via download, Power cord, Quick guide
Accessories	PM200-K (DisplayPort cable to transfer digital video and audio signals), CP200 (USB-C to DisplayPort cable), HH200PR-K (HDMI (High Definition Multimedia Interface) cable), PCSK-03 (Thin client mount)

WARRANTY	
Warranty periode	5 years for unit and LCD module up to 30,000 operating hours, whichever comes first.
Included warranty	Zero pixel defects guarantee; no fully illuminated sub- pixels (sub-pixels ISO 9241-307) for six months from date of purchase.



Experience the EV2760 in AR now!

Find your EIZO contact: EIZO Europe GmbH Belgrader Straße 2 41069 Mönchengladbach Phone: +49 2161 8210-0