



[→ Product Website](#)

Image optimisation systems

The visual evaluation of image recordings or live recordings is critically important. Be it for crime prevention, monitoring and control of infrastructure, detection of product defects, scientific image analysis and numerous other scenarios. However, recordings can be unclear due to uncontrollable circumstances. EIZO proves image optimisation can also work outside the monitor with the DuraVision EVS1VX image optimisation system. The system improves the recognisability of video recordings in the areas of security, monitoring, infrastructure maintenance and image analysis in real time. DuraVision EVS1VX is installed via HDMI between the signal source (camera or recorder) and the monitor or analysis unit and optimises playback. This simplifies the visual differentiation of image details and facilitates image analysis in AI-supported systems. Areas that are difficult to see due to low light, atmospheric haze or other environmental conditions are differentiated in real time and the brightness of each pixel is adjusted to increase detectability. This is useful not only for night or fog visibility, but also for detecting surface irregularities, such as cracks in concrete, tracks, pipes or asphalt. DuraVision EVS1VX has advanced setting options and optional features.

- ✓ Simplifies visual differentiation and easier image analysis in AI-based systems
- ✓ Installed between signal source and screen or analysis unit, video content is optimised
- ✓ 2D noise reduction filters unnatural block artefacts
- ✓ Clearer contours through 3D noise reduction (optional), especially for night shots
- ✓ Better colour differentiation of almost colourless images (optional)
- ✓ Effective adaptation to the displayed scene through extensive leveling options
- ✓ Focusing on interesting sections of the image optionally through partial image enhancement
- ✓ Capture still images of optimised scenes and save directly to USB media (optional)

Technical Data

GENERAL

Areas of application	Video surveillance, Industry
Product line	DuraVision
Areas of application	Image optimisation systems, Maritime, Video surveillance

FEATURES & OPERATION

Optional features (licence required)	capture and save still images, compression artefact reduction, advanced colour differentiation, 3D noise reduction
24/7 operation	✓
Image enhancement process	Preset, Picture section selection, Visibility Optimizer X
Video formats	1080/50p, 720/50p, 720/59,94p, 720/60p, 1080/59,94p, 1080/60p

CONNECTIONS

Signal inputs	2x HDMI (HDCP 1.4)
Signal outputs	1x HDMI
USB specification	USB 2
USB upstream ports	1 x type B
Peripheral connections	2 x Typ A
Network connection	RJ-45
Control port	USB-Protocol, Ethernet

ELECTRICAL DATA

Maximum Power Consumption [in watts]	45
Power supply	AC 100-240V, 50/60Hz

DIMENSIONS & WEIGHT

Dimensions (width x height x depth) [in mm]	240,5 x 53,2 x 143,8
Weight [in kg]	1,4
Dimension drawing (PDF)	Dimension drawing (PDF)

CERTIFICATION & STANDARDS

Operating temperature	0 - 40 °C / 20-80 % (R.H., non condensing)
Certification	CE, UKCA, CB, RCM, cTÜVus, FCC-A, CAN ICES-3 (A), VCCI-A, RoHS, WEEE

SOFTWARE & ACCESSORIES

Other box contents	AC adapter, Signal cable HDMI - HDMI, Manual via download
--------------------	---

WARRANTY

Warranty periode	2 years
------------------	---------

Find your EIZO contact:
EIZO Europe GmbH
Belgrader Straße 2
41069 Mönchengladbach
Phone: +49 2161 8210-0
www.eizo.eu