

DuraVision FDS1903-A



Product Website

The 19-inch FDF1903-A with a traditional 5:4 aspect ratio stands out thanks to its signal inputs designed for video security systems. Its HDMI input supports resolutions up to Full HD. A composite (BNC) input allows analogue video surveillance devices like cameras and recorders to be connected. The FDS1903-A provides support for PAL, SECAM and NTSC signal formats.

- High image quality for a better view
- Oisplay with high brightness level
- Computer and video inputs

- ✓ Support for NTSC/PAL/SECAM
- ✓ Underscan and normal display
- ✓ Two-year guarantee for 24/7 operation



DuraVision FDS1903-A

Technical Data

| 36 | N | E | D | ۸ | |
|----|---|---|---|---|--|

| GENERAL | |
|--|---|
| Item no. | FDS1903-ABK FDF1903-AGY |
| Case color | Black Light gray |
| Areas of application | Video surveillance, Industry |
| Product line | DuraVision |
| Areas of application | Touch and video monitors, Video surveillance |
| EAN | 4995047053965 4995047053958 |
| SCREEN | |
| Screen size [in inches] | 19 |
| Screen size [in cm] | 48 |
| Format | 5:4 |
| Viewable image size (width x height) [in mm] | 376 x 301 |
| Ideal and recommended resolution | 1280 x 1024 |
| Pixel pitch [in mm] | 0,29 × 0,29 |
| Panel technology | TN |
| Max. viewing angle horizontal | 170 |
| Max. viewing angle vertical | 160 |
| Number of colors or greyscale | 16.7 million colors (BNC, 8 bit), 16.7 million colors (HDMI, 8 Bit) |
| Max. brightness (typical) [in cd/m²] | 325 |
| Max. dark room contrast (typical) | 1000:1 |
| Backlight | LED |

FEATURES & OPERATION

| 24/7 operation | ✓ |
|------------------------------|---|
| Underscan and normal display | ✓ |
| Built-in speakers | ✓ |
| On-screen menu languages | de, en |
| Adjustment options | Signal information, Brightness, Contrast, Color temperature/White point, Colour tone, Color saturation, Viewpoint, Signal input, Volume, Blur reduction |
| Integrated power unit | ✓ |

CONNECTIONS

| Signal inputs | HDMI (HDCP 1.4), BNC | |
|----------------|---|--|
| Graphic signal | Composite Video Input, DVI Single Link (TMDS) | |
| Audio input | 3.5 mm stereo jack | |

SOFTWARE & ACCESSORIES

| Other box contents | Manual via download |
|--------------------|---------------------|

Find your EIZO contact: EIZO Europe GmbH Belgrader Straße 2 41069 Mönchengladbach Phone: +49 2161 8210-0

ELECTRICAL DATA

| Frequency | Digital: 15-68kHz/24-61 Hz |
|--|----------------------------|
| Maximum Power Consumption [in watts] | 24 |
| Max. Power consumption in stand-by mode [in watts] | 0.4 |
| Power consumption with power switch off [in watts] | 0 |
| Energy efficiency class | Е |
| Energy consumption/1000h [in kWh] | 15 |
| Power supply | AC 100-240V, 50/60Hz |
| Power management | ✓ |

DIMENSIONS & WEIGHT

| Dimensions (incl. stand) (width x height x depth) [in mm] | 405 x 407 - 507 x 205 |
|--|-------------------------|
| Weight (without stand) [in kg] | 5.9 |
| Dimension drawing (PDF) | Dimension drawing (PDF) |
| Tiltability forwards/backwards [in °] | 0/0 |
| Hole spacing | 100 x 100 |

CERTIFICATION & STANDARDS

| Operating temperature | 0 - 35 °C / 20 - 80 % (R.H., non condensing) |
|-----------------------|---|
| Certification | CE, UKCA, CB, cTÜVus, FCC-A, CAN ICES-3 (A), VCCI-A, RoHS, WEEE |

WARRANTY

| Warranty periode | 2 years |
|------------------|---------|
| | |

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries or their respective companies. Copyright © 2025 EIZO Europe GmbH, Belgrader Str. 2, 41069 Mönchengladbach, Germany. All rights, errors and modifications reserved. Latest update: 09.03.2025