

# Technical Data

GENERAL		CONNECTIONS	
Item no.	FLT	Signal inputs	USB-C (DisplayPort Alt Mode, HDCP 1.3)
Case color	Black	USB specification	USB 5Gbps (USB 3)
Areas of application	Office	USB upstream ports	1 x type C (DisplayPort Alt Mode, 60 W max.)
Product line	FlexScan	USB downstream ports	1 x type C (DisplayPort Alt Mode, 15 W max.)
Areas of application	Large and medium-sized companies, Private user & small business, Finance	Graphic signal	USB-C
EAN	4995047068907	<b>ELECTRICAL DATA</b>	
<b>SCREEN</b>		Frequency	USB Type-C: 31 - 68 kHz / 59 - 61 Hz
Screen size [in inches]	23,8	Power consumption (typical) [in watts]	6
Screen size [in cm]	60,5	Maximum Power Consumption [in watts]	94 (at maximum brightness with all signal inputs and USB ports in use)
Format	16:9	Max. Power consumption in stand-by mode [in watts]	0.27
Viewable image size (width x height) [in mm]	527 x 296,5	Energy efficiency class	A
Ideal and recommended resolution	1920 x 1080 (Full HD)	Energy consumption/1000h [in kWh]	5
Pixel pitch [in mm]	0,275 x 0,275	Power supply	AC Adapter: 100 - 240 V, 50 / 60 Hz (DC+20V±5%); USB-C: DC+4.75V ~ 5.5V
Pixel density [in ppi]	93	Max. USB-C Power Delivery [in Watt]	60
Supported resolutions	1920 x 1080 (Full HD)	<b>DIMENSIONS &amp; WEIGHT</b>	
Panel technology	IPS	Dimensions (width x height x depth) [in mm]	550,2 x 327,8 x 24,4 (Display only)
Max. viewing angle horizontal	178	Weight [in kg]	2.4
Max. viewing angle vertical	178	Dimension drawing (PDF)	<a href="#">Dimension drawing (PDF)</a>
Number of colors or greyscale	16.7 million colors (USB-C, 8 Bit)	Rotatability of the stand [in °]	180
Max. brightness (typical) [in cd/m²]	250	Tiltability forwards/backwards [in °]	40 / 40
Max. dark room contrast (typical)	1000:1	Hole spacing	100 x 100 with optional adapter plate
Response time grey-grey alternation (typical) [in ms]	5	<b>CERTIFICATION &amp; STANDARDS</b>	
Backlight	LED	Operating temperature	5 - 35 °C / 20 - 80 % (R.H., non condensing)
<b>FEATURES &amp; OPERATION</b>		Certification	CE, UKCA, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified Generation 10, TÜV/Low Blue Light Content, TÜV/Flicker Free, RCM, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA ENERGY STAR, RoHS, WEEE
USB-C docking	✓	EPEAT	EPEAT 2018 Gold (US), EPEAT Climate +
Preset color/greyscale modes	2x manual memory locations, sRGB, Eco, Paper, Movie, DICOM	<b>SOFTWARE &amp; ACCESSORIES</b>	
DICOM tone curve	✓	Accompanying software and other accessories are available for download	Screen InStyle
Auto EcoView	✓	Other box contents	Swivel arm, AC adapter, USB/signal cable (USB-C - USB-C), Power cord
EcoView Index	✓	<b>WARRANTY</b>	
EcoView Optimizer	✓	Warranty periode	5 years for unit and LCD module up to 30,000 operating hours, whichever comes first.
No flickering	✓	Included warranty	Zero pixel defects guarantee; no fully illuminated sub-pixels (sub-pixels ISO 9241-307) for six months from date of purchase.
On-screen menu languages	de, en, fr, es, it, se		

Find your EIZO contact:  
 EIZO Europe GmbH  
 Belgrader Straße 2  
 41069 Mönchengladbach  
 Phone: +49 2161 8210-0  
[www.eizo.eu](http://www.eizo.eu)

