



[→ Product Website](#)

2-megapixel medical monitor

The MX217-SB convinces with clear and high-contrast image reproduction. Thanks to the DICOM® tone curve, the monitor displays radiological images true to the object. The calibrated brightness is 240 cd/m². This makes it suitable for dental radiological reporting in room class 5 (reporting room).

- ✓ 2 megapixel colour screen with 240 cd/m² factory calibrated brightness and 500 cd/m² maximum brightness
- ✓ Clear recognition of structures through high contrast and blur reduction
- ✓ Effortless quality assurance and built-in calibration sensor for semi-automated constancy testing
- ✓ Palette with 543 billion shades for precise colour reproduction with up to 10 bits
- ✓ Hybrid Gamma PXL function for pixel-precise display of greyscale and colour images with the required luminance characteristic curve
- ✓ Homogeneous display surface due to automatic control of luminance distribution (DUE)
- ✓ Prepared for calibration, acceptance and constancy testing according to DIN 6868-157 and QS-RL
- ✓ Ergonomic design with slim housing frame
- ✓ 5-year warranty for highest investment security

Technical Data

GENERAL		CONNECTIONS	
Item no.	MX217-SB	Signal inputs	DisplayPort, DVI-D
Case color	Black	Signal outputs	1x DisplayPort (HDCP 1.2)
Areas of application	Healthcare	Daisy-chain capable	✓
Product line	RadiForce	USB specification	USB 2
Areas of application	Computed tomography/MR imagine, Dentist, Dental diagnostic room, Non-destructive-testing	USB upstream ports	1 x type B
EAN	4995047065067	USB downstream ports	2x type A
SCREEN		Graphic signal	DVI Single Link (TMDS), DisplayPort
Screen size [in inches]	21	ELECTRICAL DATA	
Screen size [in cm]	54	Frequency	Digital: 31-100 kHz/59-61 Hz
Format	3:4	Power consumption (typical) [in watts]	23
Viewable image size (width x height) [in mm]	324 x 432	Maximum Power Consumption [in watts]	54 (at maximum brightness with all signal inputs and USB ports in use)
Resolution in MP	2 Megapixels (colour)	Max. Power consumption in stand-by mode [in watts]	0.6
Ideal and recommended resolution	1200 x 1600	Power consumption with power switch off [in watts]	0
Pixel pitch [in mm]	0,27 x 0,27	Power supply	AC 100-240V, 50/60Hz
Supported resolutions	1200 x 1600	DIMENSIONS & WEIGHT	
Panel technology	IPS	Dimensions (incl. stand) (width x height x depth) [in mm]	357 x 482-572 x 200
Max. viewing angle horizontal	178	Weight (incl. stand) [in kg]	7.3
Max. viewing angle vertical	178	Dimension drawing (PDF)	Dimension drawing (PDF)
Number of colors or greyscale	1.07 billion colors (DisplayPort, 10 Bit), 16.7 million colors (DVI, 8 Bit), 16.7 million colors (DisplayPort, 8 Bit)	Rotatability of the stand [in °]	70
Color palette/look-up table	543 billion colour tones / 13 bit	Tiltability forwards/backwards [in °]	5 / 30
Max. brightness (typical) [in cd/m²]	500	Pivot between portrait / landscape	anti-clockwise
Factory calibrated brightness [in cd/m²]	240	Hole spacing	100 x 100
Max. dark room contrast (typical)	1800:1	CERTIFICATION & STANDARDS	
Backlight	LED	Certification	CE (Medical Device), UKCA (Medical Device), ANSI /AAMI ES60601-1, CSA C22.2 Nr. 601-1, EN60601-1, IEC60601-1, RCM, FCC-B, CAN ICES-3 (B), VCCI-B, RoHS, WEEE, China RoHS, CCC
FEATURES & OPERATION		SOFTWARE & ACCESSORIES	
Preset color/greyscale modes	1x manual memory location, Text, sRGB, Paper, DICOM, additional memory spaces through calibration	Accompanying software and other accessories are available for download	RadiCS LE
DICOM tone curve	✓	Other box contents	USB cable (Type A - Type B), Signal cable DisplayPort - DisplayPort, Manual via download, Power cord
Hardware calibration of brightness and light density characteristic curve	✓	Accessories	RadiCS (UX2-Kit) (The EIZO software is capable of complete quality management – from calibration through asset management to acceptance and constancy testing.), MED-XN43 (MED-XN43, optimal speed for 2D radiology), RadiNET Pro (EIZO software for network-based quality management in large facilities – with remote functionality for monitors)
Digital Uniformity Equalizer (homogeneity correction)	✓	Recommended graphics card	MED-XN43
Hybrid Gamma PXL	✓	WARRANTY	
Blur reduction	✓	Warranty periode	5 years
Sensors	Ambient Light Sensor, Integrated luminance sensor, Backlight Sensor		
On-screen menu languages	de, en, fr, es, it, se		
Adjustment options	Pathology tonal value, Brightness, Contrast, Color temperature/White point, Gamma, Color saturation, Resolution, Scaling, Skip color mode, OSD language, Signal input, Key lock, Blur reduction		
Integrated power unit	✓		



RadiForce **MX217-SB**

Find your EIZO contact:
EIZO Europe GmbH
Belgrader Straße 2
41069 Mönchengladbach
Phone: +49 2161 8210-0
www.eizo.eu

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries or their respective companies. Copyright © 2025 EIZO Europe GmbH, Belgrader Str. 2, 41069 Mönchengladbach, Germany. All rights, errors and modifications reserved. Latest update: 05.01.2025